







BUCKET

## NEW RANGE OF COMFLOR® SYSTEMS AVAILABLE




Driven by customer demand, BOSS has developed a new range of passive systems for Comflor® steel decking floor slabs. Now approved for up to 120 minutes fire resistance, BOSS's leading penetration seals now protect pipes, cables and bundled services in very thin trapezoidal floor slabs.



Tested systems in Comflor® include these leading BOSS products:

- FireMastic-HPE™ intumescent sealant
- MaxiCollars™ for pipes and cables
- BOSS Fire® Transit Box
- FireMastic-300™ 5hr fire rated sealant
- BOSS Batt

SERVICE PENETRATIONS	PRIMARY FIRE STOPPING PROTECTION	SECONDARY FIRE STOPPING PROTECTION	FRL	CERTIFICATION REFERENCE	SYSTEM
<b>Plumbing:</b>					
100mm uPVC DWV Pipe	BOSS MaxiCollar™ 100mm	BOSS Batt with Ablative Coating  BOSS FireMastic-300™	-/120/120	Warringtonfire SFC FRT180137a.2	
75mm HDPE Pipe	BOSS MaxiCollar™ 75mm	BOSS Batt with Ablative Coating  BOSS FireMastic-300™	-/120/120	Warringtonfire SFC FRT180137b.2	
32mm Copper Pipe	FireMastic-300™	N/A	-/120/30	Warringtonfire SFC FRT180137d.2	
Pipes in various combinations and quantities: - Up to 32mm PEX Pipe - Up to 32mm PEX AL Pipe - Up to 32mm Lagged Copper - Up to 32 uPVC - Up to 60mm Steel Sprinkler Pipe - Up to 25mm Uninsulated Copper	BOSS Fire® Transit Box	BOSS FireMastic-300™ P40-MAK Wrap	up to -/120/120	Branz FC12925	

BUCKET

Electrical:					
50mm Bundle of 22 x TPS Cables (2C+E)	BOSS FireMastic-HPE™	BOSS Batt with Ablative Coating	-/120/120	Warringtonfire SFC FRT180137b.2	
25mm uPVC Conduit	BOSS MaxiCollar™ 32mm	BOSS Batt with Ablative Coating BOSS FireMastic-300™	-/120/120	Warringtonfire SFC FRT180137a.2	
Cables in various combinations and quantities: <ul style="list-style-type: none"> <li>• TPS Power &amp; Mains Cables</li> <li>• Up to 32mm uPVC Conduits</li> <li>• TPS, Power &amp; Mains Cables</li> <li>• Comms &amp; Data Cables: <ul style="list-style-type: none"> <li>- CAT6, CAT5E</li> <li>- COAX Cables</li> <li>- CATV / MATV / SMATV</li> <li>- Fire Alarm &amp; Security</li> <li>- Intercom &amp; EWIS</li> <li>- A/C Control &amp; Figure 8</li> </ul> </li> <li>• AS1530.4 Appendix D cables (Exempt 630mm² Core)</li> </ul>	BOSS Fire® Transit Box	BOSS FireMastic-300™ P40-MAK Wrap	up to -/120/120	Branz FC12925	

Multi-Service Bundles & HVAC+R:					
Paircoil – A/C Lagged Copper Pipes 25mm uPVC	BOSS FireMastic-HPE™	BOSS Batt with Ablative Coating	-/120/120	Warringtonfire SFC FRT180137b.2	
Pipes in various combinations and quantities: <ul style="list-style-type: none"> <li>- Paircoil – A/C Lagged Copper Pipes</li> <li>- Up to 32mm Copper with 19mm thick lagging</li> <li>- Up to 25mm Copper with 13mm thick lagging</li> </ul>	BOSS Fire® Transit Box	BOSS FireMastic-300™ P40-MAK Wrap	up to -/120/120	Branz FC12925	

BOSS PRODUCTS:						
MaxiCollar™	FireMastic-300™	FireMastic-HPE™	BOSS Batt	BOSS Ablative Coating (Used in Conjunction with cut edges of BOSS Batt)	BOSS Fire® Transit Box	P40-MAK Wrap
						

Each project and/or application may have specific requirements and you should investigate these carefully. Ensure that you have read and understood the appropriate certification relative to your needs, and ensure you seek acceptance from the Certifying Authority or compliance inspector before installation. For updates of BOSS' certification, please contact BOSS Technical Services on +612 9531 8591.